

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 57014

1. OWNER Newmont mining Corp ADDRESS AT WELL LOCATION Twin Creeks mine
 MAILING ADDRESS P.O. Box 388 North of Golconda, NV
Valmy, NV 89438

2. LOCATION SE 1/4 SW 1/4 Sec 18 T. 39 N S R. 43 E Humboldt County
 PERMIT NO. 60057 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. DW 36 LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>Trip in Pipe to Bottom - pull back 100' - pump Super-plug Abandonment in until circulated to top, pull back 100' pump until to top again do this until all the way out to 20' pump in 246 SKS Superplug in all. 9.2 lb per gal Avg - 12 1/2 % Solids and Aprox 11, 316 gal of Slurry.</u>				
<u>Pour in 70 SKS 3/8 hole plug for 20' plug</u>				
<u>Put Cement Cap in hole with 23 SKS Cement = 15.16 per gal 216 gal Slurry.</u>				

8. WELL CONSTRUCTION
 Depth Drilled _____ Feet Depth Cased 0 Feet

HOLE DIAMETER (BIT SIZE)
 From 22 Inches 0 Feet 580 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>163/4</u>		<u>3/8</u>	<u>0</u>	<u>580</u>

Perforations:
 Type perforation Slot - well has had top portion mined OFF
 Size perforation 1/4
 From 0 feet to 580 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 20' Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No
 From Surface feet to 580 feet

9. WATER LEVEL
 Static water level 13' feet below land surface
 Artesian flow no G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality Poor

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Eklund Drilling Co Contractor
 Address P.O. Box 2748 Contractor
Eiko NV, 89803
 Nevada contractor's license number issued by the State Contractor's Board 0030823
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
 Signed [Signature] By driller performing actual drilling on site or contractor
 Date 5/17/06

Date started 5/17 2006
 Date completed 5/17 2006

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
	<u>N/A</u>	<u>no tests</u>