

Well plugged — see NOI 65330

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

OFFICE USE ONLY
Log No. 99476
Permit No. _____
Basin 137B

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 56879

1. OWNER R.M.C. ADDRESS AT WELL LOCATION ROUND MTN RD.
MAILING ADDRESS P.O. Box 480
ROUND MTN. 89045
2. LOCATION S.W. 1/4 NW 1/4 Sec. 30 T. 10 S. R. 43 E. NYE County
PERMIT NO. _____ Issued by Water Resources Parcel No. _____ Subdivision Name _____

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. #MO 2006-4 LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|-------------------------------------|--------------|-------|-------|-----------|
| CLAYS | | 0' | 200' | 200 |
| WELDED TUFFS | | 200' | 1200' | 1000 |
| VALCANAR TUFFS | | 1200' | 1500' | 300' |
| #2 SAND SUPER SAC. | | 1500' | 380' | 1120 |
| 3/8" DENTONITE CHIP 64, 50# BAGS | | 380' | 20' | 360' |
| NEVADA TYPE #1 94# BAG 5 BAGS | | 20' | 0' | 20' |

8. WELL CONSTRUCTION
Depth Drilled 1500 Feet Depth Cased 1500 Feet
HOLE DIAMETER (BIT SIZE)
From 6 1/8 Inches 20' Feet 1500' Feet
Inches _____ Feet _____ Feet
10 3/4 Inches 0' Feet 20' Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|--------------|------------|
| <u>10 3/4</u> | | <u>1/4"</u> | <u>19'</u> | <u>+1'</u> |
| <u>2"</u> | | <u>.125</u> | <u>1500'</u> | <u>+2'</u> |

Perforations:
Type perforation VERT.
Size perforation .030
From 1500' feet to 400' feet
From _____ feet to _____ feet
From BLANK 400' feet to +2' feet
From _____ feet to _____ feet
From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
Depth of Seal 20' Neat Cement
Placement Method: Pumped Cement Grout
 Poured Concrete Grout
Gravel Packed: Yes No
From 1500 feet to 380' feet

9. WATER LEVEL
Static water level 764.9 feet below land surface
Artesian flow _____ G.P.M. 12/300 S.I.
Water temperature 100 °F Quality Dirty

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name BEKUND DRILLING Co. Contractor
Address P.O. Box 2748 Contractor
ELKO NV. 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1698
Signed Jay Jones
By driller performing actual drilling on site or contractor
Date 4-25-06

Date started 3-18 2006
Date completed 3-27 2006

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|-----------|-------------------------------|----------------|
| <u>19</u> | | <u>at T.O.</u> |