

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 99631
 Permit No. _____
 Basin 648

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 56496

1. OWNER **BILL SCOTT** ADDRESS AT WELL LOCATION **TWIN BRIDGES**
 MAILING ADDRESS **2250 NO. 5TH STREET**
ELKO, NV 89801

2. LOCATION SW 1/4 SW 1/4 Sec. 30 T 32N N/S R 56E E ELKO County
 PERMIT NO. 006-290-017 **TWIN BRIDGES**
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE Rotary RVC Cable Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
TOP SOIL		0	2	
SAND & GRAVEL		2	10	8
SANDY CLAY (TAN		10	28	18
SOFT SANDSTONR		28	35	7
SAND/GRAVELw/CLAY		35	55	20
MED.SANDSTONE w/SOME		55		
CLAY			75	20
TAN CLAYw/SOME GRAVEL		75	95	20
SOFT GREY CLAY		95	130	35
CLAY & SOFT SANDSTONE		130	135	5
CLAY w/GRAVEL		135	145	10
GRAVEL w/SOME CLAY	X	145	160	15
CLAY w/SOME GRAVEL		160	245	85
GRAY CLAY & SANDSTONE		245	258	13
GRAVEL	X	258	265	7
GRAVEL w/CLAY &	X	265		
SANDSTONE			285	20
GRAVEL w/CLAY	X	285	370	85
RED CLAY & GRAVEL		370	415	45
RED CLAY		415	420	5
RED CLAY wGRAVEL		420	430	10
GRAVEL w/SOME CLAY		430	460	30
RED CLAY & GRAVEL		460	465	5
BROKEN ROCK, GRAVEL	X	465		
w/VERY LITTLE CLAY			500	35

8. WELL CONSTRUCTION
 Depth Drilled 500 Feet Depth Cased 500 Feet
 HOLE DIAMETER (BIT SIZE)
 From 10-5/8 Inches To +2 Feet 500 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6-5/8</u>	<u>13</u>	<u>.188</u>	<u>+2</u>	<u>500</u>

Perforations:
 Type perforation **SLOTS**
 Size perforation **3/16x3 6 ROW**
 From 360 feet to 380 feet
 From 440 feet to 500 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type: Neat Cement
 Depth of Seal 50 Cement Grout
 Placement Method: Pumped Poured Concrete Grout
 Gravel Packed: Yes No
 From 50 feet to 500 feet

9. WATER LEVEL
 Static water level 166 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature COLD °F Quality GOOD

Date started 1/26/06 19____
 Date completed 2/17/06 19____

7. WELL TEST DATA

TEST METHOD:	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>60</u>	<u>4</u>
G.P.M.		

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name **HACKWORTH DRILLING, INC.** Contractor
 Address **P. O. BOX 850** Contractor
ELKO, NV 89803
 Nevada contractor's license number issued by the State Contractor's Board 020582
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1166
 Signed Wale C. Veden
 By driller performing actual drilling on-site or contractor
 Date 02/20/06