STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 99702
Permit No.
Basin 029

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

*Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 56809

1. OWNER CRAIG MOORE
MAILING ADDRESS P.O. BOX 8098
STOCKTON, CA 95208

ADDRESS AT WELL LOCATION
DENIO HY 140, NEVADA

2. LOCATION NW ¼ NE ¼ Sec 25 T 44N N/S R 30 E
PERMIT/WAIVER No. 38540 (Issued by Water Resources) Parcel No.
Latitude 40.40.429
Longitude 118.34.017
UTM E N
☐ NAD 27 ☐ NAD 83
Subdivision Name: County: HUMBOLDT

3. TYPE OF WELL
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? YES
If yes, what is replacement well NO? 55495

Is there an existing well log? YES
If yes, what is NDWR well log #?

4. EXISTING WELL CONSTRUCTION
Depth Drilled 380 Feet Depth Cased 380 Feet

EXISTING CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 16 | | 1/4 | 0 | 380 |
| | | | | |
| | | | | |
| | | | | |

Existing Perforations:
Type of perforation LOUVERED
Size of perforation 3/32" X 2

| | | | |
|---|---|---|---|
| From 220 | feet to 380 | feet | |
| From | feet to | feet | |
| From | feet to | feet | |
| From | feet to | feet | |
| From | feet to | feet | |

5. WATER LEVEL
Static water level 96 feet below land surface
Artesian flow G.P.M. P.S.I
Water temperature °F Quality

Additional Notes or Comments

Punched 8 rows perforations from 0 to 220 feet
Holt Air Perforator.

Pumped Bentonite Grout from 380 feet to 20 feet using 125 bags of Abandonite.

Pumped Cement from 20 feet to surface using 25 sacks Portland.

6 WELL ABANDONMENT PROCEDURE
Was well cleaned out to total depth? ☒ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☐ yes ☒ no
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:

Additional Perforations:
Type of perforater used:

| | | | |
|---|---|---|---|
| From 0 feet to 220 feet | Number of perfs per linear foot 8 | | |
| From feet to feet | Number of perfs per linear foot | | |
| From feet to feet | Number of perfs per linear foot | | |
| From feet to feet | Number of perfs per linear foot | | |
| From feet to feet | Number of perfs per linear foot | | |
| From feet to feet | Number of perfs per linear foot | | |

7 WELL ABANDONMENT MATERIALS

| | | | Material Used | |
|---|---|---|---|---|
| From 380 feet to | 20 feet | Abandonite | ☒ Pumped | ☐ Poured |
| From 20 feet to | 0 feet | Cement | ☒ Pumped | ☐ Poured |
| From feet to | feet | | ☐ Pumped | ☐ Poured |
| From feet to | feet | | ☐ Pumped | ☐ Poured |
| From feet to | feet | | ☐ Pumped | ☐ Poured |
| From feet to | feet | | ☐ Pumped | ☐ Poured |

Neat Cement Fluid Weight lbs/gal
Bentonite Grout % bentonite

Date Started 4/28/2006
Date Completed 4/28/2006

8. DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources Nevada, Inc., dba Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4975 W. Winnemucca Blvd. (Contractor)
Winnemucca, NV 89445
Nevada contractor's license number issued by the *State Contractor's Board* 56797
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2099
Signed C Haynes - Office (By driller performing actual drilling on site or contractor)
Date 5/3/2006

(Rev. 12/03)

USE ADDITIONAL SHEETS IF NECESSARY