WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 99720
Permit No.
Basin 137B

NOTICE OF INTENT NO. 56887

1. OWNER Round Mountain Gold Corp. ADDRESS AT WELL LOCATION #1 Mine Road
MAILING ADDRESS P.O. Box 480 Round Mountain, NV 89045
Round Mountain, NV 89045

2. LOCATION NW ¼ SE ¼ Sec. 24 T. 10 N/S R. 43 E. Nye County
PERMIT NO. MIO 1402 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☒ Air ☐ Other

6. MIO-2006-1 LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium sand silts and gravel boulders		880	0	880
#8 Sand 2 3/4 / super sacks. 1 Yard bags.		880	460	420
3/8" Bentonite chips 2 3/4 / super sacks. 1 Yard bags		460	20	440
Nevada Type 2 cement 4 / 94# bags		20	0	20

Date started 5/23, 2006
Date completed 6/7, 2006

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
At TD	58		

8. WELL CONSTRUCTION
Depth Drilled 880 Feet Depth Cased 880 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 3/4	Inches	0	Feet	19	Feet
6 1/8	Inches	19	Feet	880	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8"		1/4"	+1	19
2"		1/8"	+2	880

Perforations:
Type perforation Vinyl Slot
Size perforation .020
From 480 Perf. feet to 880 feet
From feet to feet
From +2 Blank feet to 480 feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 20
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 460 feet to 880 feet

9. WATER LEVEL
Static water level 425 feet below land surface
Artesian flow NA G.P.M. NA P.S.I.
Water temperature Cold °F Quality Merky

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1698 T1
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 6/7/06

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627