WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 99722
Permit No.
Basin 066

NOTICE OF INTENT NO. 57015

1. OWNER Newmont mining Corp
MAILING ADDRESS Newmont mining Corp Hyd Dept. P.O. Box 69 Gulconda NV, 89414
ADDRESS AT WELL LOCATION Twin Creeks mine - Hyd Dept North of Gulconda, NV

2. LOCATION NE ¼ NW ¼ Sec. 18 T. 39 N/S R. 43 E. Humboldt County
PERMIT NO. (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [X] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. m/018-15B LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Oxide and Limestone from 0 to 1360				
Sulfide + Carbon (BLACK) mix with more Limestone 1360 to 1800 TD				
Set 2 3/8 (2 7/16 nominal) from -1797 to +3'				
Trimmy in 1/4 gravel from 1800 to 1450 (2 1/2 Super SKS)				
Place 3/8 hole plug from 1450 to 50' - (280 SKS 50lb)				
Pour in Cement 150 gal (12 SKS 94lb)				
Develope well with Air through trimmy - Then inject 100 gal water for every joint of Screen in each joint on way out - Stop at each Screen Pump 100 gal Pull BACK 20' Pump 100 gal etc for all 15 joints				
weld monument on				

Date started 5/19, 20 06
Date completed 6/5, 20 06

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50		

8. WELL CONSTRUCTION
Depth Drilled 1800 Feet Depth Cased 1797 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
6 1/4	0	1620
6 1/4	1620	1800

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2 3/8	3.65	1/8	+3	1797

Perforations:
Type perforation Slot
Size perforation 1/8
From 1757 feet to 1457 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50'
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 1800 feet to 1450 feet

9. WATER LEVEL
Static water level 1058 feet below land surface
Artesian flow NO G.P.M. — P.S.I.
Water temperature — °F Quality Dirty - Carbon

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Co (Contractor)
Address P.O. Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 6/5/06

(Rev. 12-01)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627