WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 99807
Permit No.
Basin 207

NOTICE OF INTENT NO. 56040

1. OWNER Carter Griffin Inc
MAILING ADDRESS Po Box 9 Lund NV 89317
ADDRESS AT WELL LOCATION Gibson Road Nye Co Lane

2. LOCATION SE ¼ SE ¼ Sec. 14 T. 10 N/S R. 61 E. NYE County
PERMIT NO. 70709 (Issued by Water Resources) Parcel No. Subdivision Name: None

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☒ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Clay Loam		0	1	
Tan Sandy clay		1	14.5	
clay gravel	water	14.5	15	
Sandy clay		15	19	
Sandy clay - gravel	water	19	20	
tan Sandy Clay		20	55	
Sandy Clay - gravel	water	55	60	
Sandy Clay - gravel		60	68	
Clay gravel	water	68	69.5	
Sandy clay		69.5	90.5	
gravel Fine sand	water	90.5	91.5	
Sandy Clay		91.5	95.5	
gravel	water	95.5	99.5	
Sandy Clay		99.5	115	
Sand	water	115	116	
Clay		116	118	
Sand	water	118	120	
Clay		120	127	
Sand	water	127	130	
Clay		130	150	
Sand	water	150	152	
Clay		152	160	
Sand	water	160	161	
Clay		161	200	

Date started Dec 16 2005
Date completed Febuary 21 2006

7. WELL TEST DATA
TEST METHOD: ☒ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
100	0	1

8. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
20 Inches		0 Feet	130 Feet
16 Inches		130 Feet	200 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		.250	-1	200

Perforations:
Type perforation mill
Size perforation 1/8 x 3.5 x 16 row
From feet to feet
From 50 feet to 200 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 130 feet

9. WATER LEVEL
Static water level 12 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Maynard Well Drilling (Contractor)
Address Po Box 64 Lund NV 89317 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 47226
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1556
Signed [signature] (By driller performing actual drilling on site or contractor)
Date March 7-06

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627