Also SEE Log. 1143.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1143
Rec. 12/9 19 49
Well No.
Permit No.
Do not fill in

Owner: Slim Olsen, Inc.
Driller: J. H. Peterson
Address: Elko Nev.
Address: Bountiful Utah
Lic. No. -

Location of well: SE 1/4 NW 1/4 Sec. 20, T. 34 (N) S, R 55 E, in Elko County

or

Water will be used for
Total depth of well 274

Size of drilled hole
Weight of casing per linear foot

Thickness of casing
Temp. of water

Diameter and length of casing 8 5/8" on/well -
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 15'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Oct 20 - 49
Date of completion of well Nov. 12 - 49

Type of well rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	Surface & clay
28	31	3	gravel (sur. water)
31	62	31	sand clay & pea gravel
62	65	3	~~pea gravel (water)~~ clay
65	75	10	pea gravel (water
75	86	11	clay
86	106	20	sand gravel & clay
106	162	56	clay
162	170	8	pea gravel (water)
170	245	75	clay
245-~~274~~	274	29	gravel (interlaid with clay strata & coarse gravel carrying water.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.
~~245~~ 245 to 274

Chief aquifer (water-bearing formation)
from to ft.

Other aquifers

First water at feet.

Casing perforated
from 240 to 268 ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

bailing test 50 gpm 45' drawdown.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No.....

Dated....., 19.....

(Not to be filled in by Driller)