

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 1287  
 Rec. 4/7/50 1950  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Gorden Dey Driller Mel Meyer  
 Address Washoe Valley, nev. Address 120 Moana Lane Reno, Lic. No. 3  
 Location of well: NE 1/4 N 1/4 Sec. 11, T. 17 N/S, R. 19 E, in Washoe County  
 or WASHOE VALLEY  
 Water will be used for House Total depth of well 85'  
 Size of drilled hole 6" Weight of casing per linear foot 20#  
 Thickness of casing 5/16 Temp. of water Cald  
 Diameter and length of casing 6" id 82'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 6'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well 4-9-50 Date of completion of well 4-II-50  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	5	5	Top Soil	
5	35	30	Sandy Clay	
35	45	10	Coarse Sand (good flow water)	Chief aquifer (water-bearing formation)
45	70	25	Sandy Clay	from <u>70</u> to <u>85</u> ft.
70	85	15	Sand & Water	Other aquifers _____ <u>35-45</u>
				First water at <u>35</u> feet.
				Casing perforated from <u>70</u> to <u>80</u> ft.
				Size of perforations <u>4" cutting torch</u> <u>12 slots</u>

