WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1292
Rec. 5/19 1950
Well No.
Permit No.
Do not fill in

Owner: Andrew Pedretti Driller: Kel Meyer

Address: C. Wassor & Kietzke Lane Reno, Address: 120 Moana Lane Reno, Lic. No. 3

Location of well: ~~1/4~~ 1/4 Sec. 12, T. 19 N/S, R. 20 E, in Washoe County

or Rear of New Home.

Water will be used for Home Total depth of well 65'

Size of drilled hole Weight of casing per linear foot 188

Thickness of casing 5/16 Temp. of water Cold

Diameter and length of casing 6"id x 65'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 10'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 4-12-50 Date of completion of well 4-14-50

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	13	13	Clay-Rock
13	16	3	Sand (water)
16	34	18	Rock-Sand
34	37	3	Clay
37	54	17	Rock-Sand (water)
54	65	11	Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 37 to 54 ft.

Other aquifers 13-16
37-65

First water at 13 feet.

Casing perforated

from 50 to 63 ft.

Size of perforations

2½ x1/4 x 15 cuts

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	65	65	Std Steel w/t case hard shoe welded joints

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Air Compressor 8 hrs

30 gp m

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Mel Meyer
Well Driller

By Mel Meyer

License No. 3

Dated 4-23-50, 19

OFFICE STATE ENGINEER MAY 10 50

(Not to be filled in by Driller)