

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1399  
 Rec. 8/14/1930  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner A.H. CLIFE Driller HARVEY MEYER  
 Address WASHOE VALLEY Address CARRSON CITY Lic. No. 10  
 Location of well: SE 1/4 SE 1/4 Sec. 15, T. 16 N/S, R. 19 E, in WASHOE VALLEY County \_\_\_\_\_  
 or DAIRY  
 Water will be used for Domestic Total depth of well 131  
 Size of drilled hole 6" Weight of casing per linear foot 20 LBS  
 Thickness of casing 5/16 Temp. of water 60  
 Diameter and length of casing 6" — 131  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure NO  
 If nonflowing well give depth of standing water from surface 4 FEET  
 If flowing well describe control works NO  
(Type and size of valve, etc.)  
 Date of commencement of well July 9 Date of completion of well July 14  
 Type of well rig CABLE TOOLS

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	DIRTY LOAM	
3	34	31	GRANIT. SAND CLAY	Chief aquifer (water-bearing formation) from <u>60</u> to <u>74</u> ft.
34	47	13	WATER SAND.	Other aquifers _____
47	60	13	SANDY CLAY.	
60	74	14	SAND WATER.	
74	112	38	SANDY CLAY.	
112	131	19	GRANIT. SAND.	First water at <u>3</u> feet.
				Casing perforated from <u>60</u> to <u>70</u> ft.
				Size of perforations <u>B/8</u>

