# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1466
Rec. 10/30 1950
Well No.
Permit No.
Do not fill in

Owner R. J. Raymond — Driller HARVEY MEYER
Address Washoe Valley — Address ORMSBY — Lic. No. 10
Location of well: NE ¼ NE ¼ Sec. 10, T. 12 N/S, R. 19 E, in WASHOE County
or
Water will be used for Stock — Total depth of well 138'
Size of drilled hole 6" — Weight of casing per linear foot 20 LBS.
Thickness of casing 5/16 — Temp. of water COOL
Diameter and length of casing 6" —— 138'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure 10 GAL PER MINUTE
If nonflowing well give depth of standing water from surface FLOWING
If flowing well describe control works Piped in STOCK TANK
(Type and size of valve, etc.)
Date of commencement of well Oct. 10 — Date of completion of well OCT. 14
Type of well rig CABLE TOOLS

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|---|---|---|---|
| Old Well Drilled Down — | | | |
| 0 | 114 | | SAND — |
| 114 | 122 | 8 | CLAY |
| 122 | 138 | 16 | GRANIT SAND |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 122 to 138 ft.
Other aquifers

First water at 0 feet.

Casing perforated
from 0 to 15 ft.

Size of perforations
1/8

(OVER)

LOG OF FORMATIONS—*Continued*

| From feet | To feet | Thickness | Type of material |
|---|---|---|---|
| | | | |

CASING RECORD

| Diam. casing | From feet | To feet | Length | "Remarks"—Seals, Grouting, Etc. |
|---|---|---|---|---|
| | | | | |

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL WILL MAKE 10 GALLONS PER MINUTE FLOWING

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harvey Myer
Well Driller

By Harvey Myer

License No. 10

Dated Oct. 14, 1950

OFFICE STATE ENGINEER
OCT 30 50
RECEIVED
ANS.

(Not to be filled in by Driller)