

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1509 ✓
 Rec. 12/28 1950
 Well No.
 Permit No.
Do not fill in

Owner Edmund Giles Driller L. M. Parnell
 Address Thymothy Lane Address Marine Hotel Lic. No. 29
 Location of well: $\frac{1}{4}$ Sec. 12, T. 17 N. 8, R. 9 E, in Hatch County

Water will be used for Domestic Well Total depth of well 210
 Size of drilled hole 6" Weight of casing per linear foot
 Thickness of casing Temp. of water cold
 Diameter and length of casing
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 11 feet
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well Sept 30, 1950 Date of completion of well Oct 5, 1950
 Type of well rig Rayburn C. rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Ballston
20	35	15	clay & sand
35	40	5	sandy water
40	95	55	clay sand
95	97	2	30 lb water
97	120	23	clay sand
120	121	1	shovel
121	170	49	sand
170	175	5	clay & clay
175	195	20	sand gravel
195	200	5	clay gravel
200	210	10	clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from to ft.

Other aquifers

First water at feet.

Casing perforated
 from 155 to 175 ft.

Size of perforations
3/16"



