WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1767
Rec. 10/16 1951
~~Well No.~~ Basin 131
Permit No. 14916
Do not fill in

Public Grazing Permit No. N-1-90
Julian Borecha Range #58

Owner: Taylor Grazing drill Driller: Glenn Kidd
Address: Ely, Nevada Address: Mt City, Nev Lic. No. 108

Location of well: ~~NW~~ SE ¼ ~~NW~~ SE ¼ Sec. ~~14~~ 13, T. 23 N/S, R. ~~58~~ 57 E, in White Pine County County
or North end of Mooney basin close to road range 58E

Water will be used for: Stock water Total depth of well: 270

Size of drilled hole: 7 in Weight of casing per linear foot: 18 lbs per foot

Thickness of casing: 5/16" Temp. of water: Cold

Diameter and length of casing: 6" casing - ~~270~~ ft random lengths used
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: 0

If nonflowing well give depth of standing water from surface: 235 ft from surface

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 6th August Date of completion of well: 10th Sept

Type of well rig: Chum drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	top soil & boulders
6	46	40	clay some rock & gravel
46	130	84	mostly clay some gravel
130	165	35	little more gravel - clay
165	195	30	greater % rock - clay gravel & coarse sand clay
195	230	35	~~to clay - some gravel~~
230	245	15	Mostly gravel little clay water at 245
245-270	270	25	gravel & coarse sand more water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 245 to 270 ft.

Other aquifers: None — Coarse sand & Gravel

First water at 245 feet.

Casing perforated
from 255 to 278 ft.

Size of perforations
½ x 3

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 inch	0	268-4	268'4"	
8 inch	0	-12	12'	seal with clay

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Water stayed at 250' from surface bailing as fast as machine would go with 9 gallon bailer making trip every 110 to 120 seconds)

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Gerald D. Kidd
Well Driller

By

License No. 108

Dated Sept 24, 1957

OFFICE STATE ENGINEER
OCT 1 1957
RECEIVED
ANS

(Not to be filled in by Driller)