LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	238	238	Black steel seamless casing

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Making approx. 30 gal. per minute with 100' draw down.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed John Champion
Well Driller

By .....

License No. 29

Dated....., 194.....

(Not to be filled in by Driller)

OFFICE STATE ENGINEER
FEB 11 '52
RECEIVED

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. ~~Feb.~~ 1853
Rec. Feb 11 1952
Well No.
Permit No.
Do not fill in

Owner Leslie B. Gray Driller John Champion

Address 210 Wedekind Rd. Sparks Address Lic. No.

Location of well: ¼ SE ¼ Sec. 31, T. ~~19~~ 20 N/S, R. 20 E, in Washoe County

or

Water will be used for Domestic Total depth of well 240

Size of drilled hole 6" Weight of casing per linear foot 20

Thickness of casing Temp. of water Cold

Diameter and length of casing 6" X 238'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 35'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Nov 1st 1951 Date of completion of well Nov 7th 1951

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	44	44	Sandy clay
44	[illegible]	1	Sand
45	126	81	Sandy clay
126	127	1	Sand
127	220	93	Sandy clay
220	235	15	Sand
235	[illegible]	5	Rock

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 220 to 240 ft.

Other aquifers 44 to 45

First water at 44 feet.

Casing perforated

from 218 to 238 ft.

Size of perforations

1/8" x 4"