

**WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA**

Log No. 1907  
 Rec. May 15 1952  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner A. Passback Driller J. E. Faretto & Son  
 Address 1300 W. 2nd St, Reno Address 736 Humboldt St, Reno Lic. No. 2  
 Location of well: SE 1/4 SW 1/4 Sec. 10, T. 19 N, R. 19 E, in Truckee Meadows, Washoe County  
 or 1/4 mile west from end of W. 2nd St, in Reno on Dickerson Road  
 Water will be used for Domestic Total depth of well 33 ft  
 Size of drilled hole 6 inch Weight of casing per linear foot 19.18 lbs.  
 Thickness of casing .280 of an inch Temp. of water 56°  
 Diameter and length of casing 6" inside diameter. 4'-10" to 8'-03" lengths  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....  
 If nonflowing well give depth of standing water from surface 9'-08"  
 If flowing well describe control works.....  
 (Type and size of valve, etc.)  
 Date of commencement of well April 11, 1952 Date of completion of well April 17, 1952  
 Type of well rig Cable Tool Rig

**LOG OF FORMATIONS**

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	Black soil.	
3	30	27	Rocks, yellow clay with coarse sand & gravel.	Chief aquifer (water-bearing formation)
30	32	2	1st water, Water level 7'-05". Little water.	from <u>32</u> to <u>33</u> ft.
32	33	1	Coarse sand & coarse gravel, stony, rocky, with yellow clay. Loose. 2nd water, Water level 9'-08". Little water. Coarse sand, rocky & bolders,	Other aquifers .....
				First water at <u>30</u> feet.
				Casing perforated from ..... to ..... ft.
				Size of perforations .....



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	2'-00"	33'-00"	35'-00"	Standard black pipe. Welded couplings 1/4" x 3". Blacksmith made short pattern shoe.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Sand material black. Gravel washed and smooth and rounded. Well tested and cleaned with bailer 5 gal per min. 10 ft drawdown.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J.C. Faretto & Son  
Well Driller

By Harold J. Faretto

License No. 2

Dated May 5, 19 52

(Not to be filled in by Driller)

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

