WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1959 [illegible]
Rec. 6/3 1952
Well No.
Permit No.
Do not fill in

Owner W S Wright Driller W S Wright

Address Dyer Nevada Address Dyer Nevada Lic. No. 5

Location of well: sw ¼ sw ¼ Sec 5, T. 4S N/S, R 36 E, in Esmeralda Count

or about 150 ft from thewest line and 50 ft north from the south line

Water will be used for domestic Total depth of well 87 ft

Size of drilled hole 15 " Weight of casing per linear foot 12#

Thickness of casing 12 ga Temp. of water 56

Diameter and length of casing 10¼ "O) D 10" I D
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 29 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well June 1 1952 Date of completion of well June 3 1952

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
top	26	26	sandy loam
26	46	20	coarse sand
46	58	12	sandy clay- brown
58	87	29	sand gravel& rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 29 to 46 ft.

Other aquifers 58 to 87

First water at 29 feet.

Casing perforated

from 40' to 87 ft.

Size of perforations

3/16 by 5"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
	top	87	21	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

This well was tested with a 60 gal bailer and will produce about 50 gals P.M. also the well was graveled with screened gravel, using about 5 tons.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed W S Wright sr
Well Driller

By W S Wright sr

License No. 56

Dated June 26, 1952

OFFICE STATE ENGINEER
JUN 30 '52
RECEIVED
ANS.

(Not to be filled in by Driller)