WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2083
Rec. Oct. 24 1952
Well No.
Permit No. 14600
Do not fill in

Owner: Pete Delmue + Frank Delmue Driller: Darell Tree

Address: Rioche Nevada Address: Rioche Nev. Lic. No. 30

Location of well: S.E.¼ S.E.¼ Sec. 6, T. 1 N/S, R 69 E, in Lincoln County

or

Water will be used for: Irrigation Total depth of well: 100 ft.

Size of drilled hole: 12 in. Weight of casing per linear foot

Thickness of casing: 12 Gauge Temp. of water

Diameter and length of casing: 12 in 96 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 17 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: Sept. 24, 1952 Date of completion of well: Sept 30, 1952

Type of well rig: Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Gravel
4	42	38	Clay
42	61	19	Gravel
61	62	1	Clay
62	92	30	Gravel
92	100	8	Gravel in Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 42 to 92 ft.

Other aquifers

First water at 17 feet.

Casing perforated
from 16 to 96 ft.

Size of perforations
1/8 x 12 in.

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

This well was tested by E. M. Calvin of Cedar City Utah. approx. 600 gal. p.m. from 40 ft. possible 800 gals. p.m. from 60 ft. Will forward copy of well test if received.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed ✓
Well Driller

By Darell Free

License No. 30

Dated Oct 21, 1952

OFFICE STATE ENGINEER OCT 24 '52 RECEIVED

(Not to be filled in by Driller)