


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2239  
 Rec. June 3 1952  
 Well No. ....  
 Permit No. ....



Owner Fred Palm Driller HANS. A. M.  
 Address Dyer Nev Address Dyer Nev Lic. No. 113  
 Location of well: SW 1/4 NW 1/4 Sec. 15, T. 2-SN/S, R. 35-E, in ESMERALDA Cour

Water will be used for Domestic Total depth of well 84'

Size of drilled hole 9 1/4" Weight of casing per linear foot.....

Thickness of casing 12 ga Temp. of water.....

Diameter and length of casing 8" - 84'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 44'

If flowing well describe control works.....  
(Type and size of valve, etc.)

Date of commencement of well..... Date of completion of well Nov 20 52

Type of well rig Cable tool

### LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|------------------|
| 0         | 37      | 37             | SANDY CLAY       |
| 37        | 54      | 17             | SAND & GRAVEL    |
| 54        | 58      | 4              | CLAY             |
| 58        | 82      | 24             | GRAVEL & ROCK    |
| 82        | 84      | 2              | CLAY             |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 42 to 54 ft.

Other aquifers 58-82

First water at 42 feet.

Casing perforated

from 52 to 82 ft.

Size of perforations

1/8 x 1 1/2



