LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	32	32'	20 gauge galvinized Casing + Screened Cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

1/4 HP Pressure System.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Erb.
Well Driller

By Mrs Fred Erb.

License No.

Dated Jan. 14, 1954

OFFICE
STATE ENGINEER
FEB 26 54
RECEIVED
ANG

(Not to be filled in by Driller)

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2476
Rec. Feb 26 19 54
Well No.
Permit No.
Do not fill in

Owner: Emmit Larsen Driller: Fred Eub.
Address: Address: East Star Rt. Fallon Nev. Lic. No. 121

Location of well: S.E. ¼ S.E. ¼ Sec. 19, T. 19 N/S, R. 29 E, in Churchill County

or

Water will be used for: Domestic Total depth of well: 32 feet,

Size of drilled hole: 6 inch Weight of casing per linear foot:

Thickness of casing: Temp. of water: 60°.

Diameter and length of casing: 6 inch Casing 32 ft long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 19 feet.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Feb 2 54 Date of completion of well: Jan 12, 1954.

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	adobe
2	18	16	Sand.
18	20	2	adobe
20	32	12	Sand.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.
Sand.

Chief aquifer (water-bearing formation)
from 20 to 32 ft.

Other aquifers:

First water at 20 feet.

Casing perforated
from 26 to 32 ft.

Size of perforations
1" x 1/64"

919