WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2587
Rec. June 14 1954
Well No.
Permit No.
Do not fill in 039

Owner L. B. MEYER. Driller HARVEY MEYER

Address NEW EMPIRE. Address CARSON CITY Lic. No. 10

Location of well: NW ¼ NE ¼ Sec. 9, T. 16 N/S, R. 20 E, in ~~ORMSBY~~, Washoe County

or

Water will be used for DOMESTIC Total depth of well 68'

Size of drilled hole 6" Weight of casing per linear foot 12 LBS.

Thickness of casing 3/16 Temp. of water COOL.

Diameter and length of casing 6" — 68'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure NO

If nonflowing well give depth of standing water from surface 11'

If flowing well describe control works NO
(Type and size of valve, etc.)

Date of commencement of well JUNE 1. Date of completion of well JUNE 2.

Type of well rig CABLE TOOLS

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	HARD PAN.
4	23	19	SANDY CLAY.
23	28	5	SAND-WATER.
28	46	18	SANDY CLAY.
46	68	22.	SAND-WATER.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 46' to 68' ft.

Other aquifers

First water at 23 feet.

Casing perforated
from 52' to 68' ft.

Size of perforations
1/8.

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL WILL MAKE 18 GPM
HAL-PER BAILING TEST

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harry Meyer
Well Driller

By Harry Meyer

License No. 10

Dated JUNE 2, 19 54

OFFICE STATE ENGINEER
JUN 14 '54
RECEIVED

(Not to be filled in by Driller)