Need copy

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3025
Rec. 19
Well No. .....
Permit No. 15965
Do not fill in

Owner: Dr. D.D. Carr
Driller: S.R. McKinney & Son
Address: 300 Decator Lane, Las Vegas, Nev
Address: 1042 So. Main, L.V. Lic. No. 45

Location of well: SE ¼ SE ¼ Sec. 24, T. 20 N/S, R. 60 E, in Clark County

or .....

Water will be used for: Domestic
Total depth of well: 250'

Size of drilled hole: 12" to 50, 10" to 250'
Weight of casing per linear foot: 28 lb.

Thickness of casing: ¼" wall
Temp. of water: .....

Diameter and length of casing: 8" I.D. casing to 242
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: .....

If nonflowing well give depth of standing water from surface: 37'

If flowing well describe control works: .....
(Type and size of valve, etc.)

Date of commencement of well: June 1, 1955
Date of completion of well: June 8, 1955

Type of well rig: Bucyrus Erie 24L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Topsoil
3	14	11	Caliche
14	18	4	White Clay
18	29	11	Caliche
29	38	9	White Clay
38	43	5	Caliche Water
43	70	27	Red Sandy clay
70	75	5	Caliche
75	80	5	Red sand water
80	87	7	Red sand water
87	90	3	Sand Stone
90	117	27	Sandy clay with hard shelfs
117	123	6	Red sand water
123	130	7	Red sandy clay
130	140	White	clay
140	165	25	Red sandy clay
165	180	15	Cemented gravel water
180	204	24	loose Gravel with thin layers of cemented gravel water
204	242	38	Loose Gravel with layers of cemented gravel water
242	250	8	Gravel Water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 242 to 250 ft.

Other aquifers: 204' to 242'
180' to 204' 75' to 80'
165' to 180' 38' to 43'
117' to 123'
80' to 87'

First water at 38' feet.

Casing perforated
from 170 to 250 ft.

Size of perforations: 3/16" x 10"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" I.D.	0	251	251	8" casing cemented down to 80 ft. with 4 yds. concrete.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 70 G.P.M. from 65 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed S. R. McKinney & Son
Well Driller

By [illegible]

License No. 45

Dated June 20, 1955

(Not to be filled in by Driller)

JUN 24 AM 9 23
STATE ENGINEER OFFICE