

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

Log No. 3068  
 Rec. July 28 19 55  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner H. L. Mankangher Driller J. B. Reynolds  
 Address Ruby Valley Address Fallon Lic. No. 28  
 Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. 19, T. 29 N/S, R. 59 E, in Elko County

Water will be used for stock watering Total depth of well 40'  
 Size of drilled hole 6" six inch Weight of casing per linear foot 10 gage Redytul  
 Thickness of casing 10 gage Temp. of water cold, some sulphur.  
 Diameter and length of casing 6" X 40'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 8'  
 If flowing well describe control works \_\_\_\_\_ (Type and size of valve, etc.)  
 Date of commencement of well July 20/55 Date of completion of well July 20/55  
 Type of well rig Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	6	6	silt & sand	
6	40	34 3	Blue clay water in blue clay lots of it. But has a strong sulphur odor.	Chief aquifer (water-bearing formation) from <u>8</u> to <u>40</u> ft. Other aquifers <u>none</u>
				First water at _____ feet.
				Casing perforated from _____ to _____ ft.
				Size of perforations _____

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	Remarks—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Installed 1 1/2" centrifugal pump.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed

*J.P. Reynolds*  
Well Driller

By

License No. 28

Dated

July 23, 1955

(Not to be filled in by Driller)

OFFICE  
STATE ENGINEER