WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3069
Rec. July 28 1955
Well No.
Permit No.
Do not fill in

Owner: Ray Still
Address: Ruby Valley
Driller: J. B. Reynolds
Address: Salt Lake City
Lic. No. 28

Location of well: ¼ ¼ Sec. 32, T. 30 N/S, R. 59 E, in Elko County
or one hundred feet west of Ray Stills shop in Ruby Valley.

Water will be used for: Domestic
Total depth of well: 115
Size of drilled hole: 6" six inch
Weight of casing per linear foot: 12 lbs
Thickness of casing: 5/16"
Temp. of water: cold
Diameter and length of casing: 6" X 115'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 62' sixty two ft.
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well: July 4/55
Date of completion of well: July 15/55
Type of well rig: Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	Gravel & clay
28	63	35	Decomposed Granite & clay
63	102	39	Gravel & clay
102	115	13	water bearing sand stone

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 102 to 115 ft.
Other aquifers: 28 deep
small amount
at 63 ft.

First water at 28 feet.

Casing perforated
from 83 to 115 ft.

Size of perforations
¼" X 1½

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pumped 20 G.P.M. for one hour. water drew down to 68'. one six feet draw down.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. R. Runolda
Well Driller

By

License No. 28

Dated July 23, 1955

OFFICE
STATE ENGINEER

1955 JUL 28 AM 9 43

(Not to be filled in by Driller)