WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3073
Rec. Aug. 3 1956
Well No.
Permit No. 15819
Do not fill in

Owner: Gordon Beetles
Driller: The B & B Drilling Co.
Address: Lathrop Wells Nevada
Address: Beaver, Utah
Lic. No. 193

Location of well: N ¼ NW ¼ Sec. 11, T. 13 S, R. 49 E, in Nye County

or

Water will be used for: Irrigation
Total depth of well: ~~185~~ 185

Size of drilled hole: 15 inch
Weight of casing per linear foot: 224

Thickness of casing: 3/16
Temp. of water:

Diameter and length of casing: 10 inch 160 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 45 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: March 9, 1955
Date of completion of well: March 11, 1955

Type of well rig: Rotory

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	26		Surf.
26	44		Clay
44	48		Gravel Sand
48	62		Clay Boulders
62	69		Sand Gravel
69	78		Boulders Clay
78	85		Sand Gravel
85	91		Boulders Clay
91	141		Sand Gravel
141	144		Boulders Clay
144	185		Sand Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 91 to 141 ft.

Other aquifers

First water at 45 feet

Casing perforated
from 45 to 160 ft.

Size of perforations
1/8 to 3/16

(OVER)

919