WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3216
Rec. OCT. 28 1955
Well No.
Permit No.
Do not fill in

Owner: Quinn river Ranch Driller: [illegible]

Address: Winnemucca Nev Address: [illegible] Lic. No. 4307

Location of well: SW ¼ NW ¼ Sec. 13, T. 46 N/S, R. 30 E, in Humboldt County

or

Water will be used for [illegible] Total depth of well 194

Size of drilled hole 8 in Weight of casing per linear foot [illegible]

Thickness of casing ¼ Temp. of water

Diameter and length of casing 8 in 189'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 110

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 8/26 Date of completion of well 9/28

Type of well rig Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	[illegible]	Fine Sand
18	36	18	Fine Sand Trace clay
36	40	4	Silt Trace gravel
40	187	147	Fine Sand, Trace clay
187	189	2	Heavy clay
189	191	1	[illegible]
[illegible]	[illegible]	2	[illegible] gravel
[illegible]			Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 191 to 194 ft.

Other aquifers

First water at 155 feet.

Casing perforated

from 0 to ft.

Size of perforations

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8	0	189	189	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump 700 gal Per Hr

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Rich Knoblock
Well Driller

By

License No. 4307

Dated 9/30, 1955

OFFICE
STATE ENGINEER

1955 OCT 28 AM 10 59

(Not to be filled in by Driller)