

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3268
 Rec. Dec. 19 19 55
 Well No.
 Permit No.

Do not fill in

Owner Leslie C. Smith Driller MEL MEYER COMPANY

Address 1002 Kietzke Lane Reno, Nev. Address 190 Moana Lane Reno Lic. No. 3
West Half

Location of well: 1/4 NW 1/4 Sec. 18, T. 19 N/S, R. 20 E, in Washoe County
 or

Water will be used for Domestic Total depth of well 50'

Size of drilled hole 6 5/8" Weight of casing per linear foot 17.02

Thickness of casing .250 Temp. of water Cold

Diameter and length of casing 6" X 51'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 18'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well 7/5/55 Date of completion of well 7/7/55

Type of well rig Cable Tool

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material | Water-bearing Formation, Casing Perforations, Etc. |
|-----------|---------|----------------|--------------------------|--|
| 0 | 26 | 26 | Boulders, Sand, and clay | Chief aquifer (water-bearing formation) from <u>26</u> to <u>50</u> ft. Other aquifers |
| 26 | 41 | 15 | Sand and Water | |
| 41 | 50 | 9 | Sand | |
| | | | | First water at <u>26</u> feet. |
| | | | | Casing perforated from <u>32</u> to <u>50</u> ft. |
| | | | | Size of perforations <u>1/8 X 6" X 6"</u> |

