WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3316
Rec. Feb. 9 1956
Well No.
Permit No. 16717
Do not fill in

Owner: George Etchart and/or Pauline Etchart
Driller: William Flynn
Address: Winnemucca, Nevada
Address: Box 26 Sutter, Calif. Lic. No. 162

Location of well: NE ¼ NE ¼ Sec. 28, T. 38 N/S, R. 39 E, in Humboldt County

or

Water will be used for: Irrigation & Domestic
Total depth of well: 327 Ft.

Size of drilled hole: 12"
Weight of casing per linear foot:

Thickness of casing: 3/16"
Temp. of water:

Diameter and length of casing: 12" I.D. 327Ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: Non-Flowing

If nonflowing well give depth of standing water from surface: 11 Ft.

If flowing well describe control works: None
(Type and size of valve, etc.)

Date of commencement of well: October 16, 1955
Date of completion of well: December 2, 1955

Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Soil
18	327	309	Sandy Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 18 to 327 ft.

Other aquifers

First water at 18 feet.

Casing perforated
from 100 to 327 ft.

Size of perforations
1/4" x 2"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
12" I.D.	0	327	327	None

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Tested at 1500 Gallons per minute at fourty feet. Good.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Wm T Lynn
Well Driller

By.....

License No. 162

Dated Feb. 3, 19 56

(Not to be filled in by Driller)

OFFICE
STATE ENGINEER

1956 FEB 6 AM 8 17