Need copy

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3356
Rec. March 8 1956
Well No.
Permit No.
Do not fill in

Hollywood Vegas, Inc. (Lou Fogg)

Owner

Driller Effinger Bros. Box 589 212

Address

Address Clark Lic. No.

Location of well: NW¼ Section 35 T20S R60E 62 N/S, R. E, in Marys Road County

or Domestic 380 feet

Water will be used for 12 Inch Total depth of well 12.06 lbs.

Size of drilled hole 10 Guage Weight of casing per linear foot

Thickness of casing 8"OD 380 feet Temp. of water

Diameter and length of casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure 82.5 feet from top of casing

If nonflowing well give depth of standing water from surface

If flowing well describe control February 14, 1956 March 5, 1956
(Type and size of valve, etc.)

Date of commencement of well "71 Speed Star" Date of completion of well

Type of well rig

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|---|---|---|---|
| 0 | 21 | 21 | Gravel |
| 21 | 65 | 44 | Brown Clay |
| 65 | 83 | 18 | White Clay |
| 83 | 113 | 30 | Red Clay |
| 113 | 120 | 7 | Yellow Clay |
| 120 | 122 | 2 | Gravel (Water) |
| 122 | 132 | 10 | Yellow Clay & Gravel |
| 132 | 136 | 4 | Limestone |
| 136 | 168 | 32 | Clay & Gravel |
| 168 | 169 | 1 | Limestone (Water) |
| 169 | 185 | 16 | Brown Clay & Gravel |
| 185 | 235 | 50 | Yellow Clay & Gravel |
| 235 | 236 | 1 | Blue Clay |
| 236 | 251 | 15 | Yellow Clay & Gravel |
| 251 | 277 | 26 | White Sand & Gravel (Water) |
| 277 | 289 | 12 | Yellow Clay & Gravel |
| 289 | 295 | 6 | White Sand & Gravel (Water) |
| 295 | 330 | 35 | White Clay & Gravel |
| 330 | 365 | 35 | Yellow Clay & Gravel |
| 365 | 369 | 4 | Blue Clay |
| 369 | 376 | 7 | White Sand & Gravel (Water) |
| 376 | 380 | 4 | Red Clay |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation) 369 376

from 289-295 ft.

Other aquifers 251-277
168-169
120-122

120

First water at feet.

120 380
Casing perforated

from to ft.

1/8 X 50
Size of perforations

LOG OF FORMATIONS—*Continued*

| From feet | To feet | Thickness | Type of material |
|---|---|---|---|
| | | | |

CASING RECORD

| Diam. casing | From feet | To feet | Length | "Remarks"—Seals, Grouting, Etc. |
|---|---|---|---|---|
| 8"OD | 0 | 380 | 380 | Cemented from 0 to 70 feet<br>3½ yards of cement<br>Graveled packed from 70 to 380 feet<br>13 yards of pea gravel |

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 600 gallons in 30 minutes

Lowered well from 82.5 to 140 feet

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Effinger Bros.
Well Driller

By

License No. 212

Dated March 5, 1956

(Not to be filled in by Driller)

OFFICE