WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3391
Rec. May 8 1956
Well No.
Permit No.
Do not fill in

Owner: E. C. FLYNN
Driller: J. W. CUNNINGHAM
Address: OLD CARSON CITY ROADE
Address: MOANA LANE Lic. No. 180

Location of well: ¼ ¼ Sec. 10, T. 18 N/S, R. 20 E, in WASHOE County

or

Water will be used for: DOMESTIC
Total depth of well: 110 FEET

Size of drilled hole: 6"
Weight of casing per linear foot: 13 POUNDS

Thickness of casing: 3/16"
Temp. of water: COLD

Diameter and length of casing: 6" RANDOM LENGTHS
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 65 feet

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: April 5, 1956
Date of completion of well: April 16, 1956

Type of well rig: KEYSTONE

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	38	38	BOULDERS
38	60	22	CLAY
60	72	12	WATER SAND
72	90	18	CLAY
90	95	5	WATER SAND
95	110	15	HARD PAN

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 60 to 72 ft.

Other aquifers

First water at 65 feet.

Casing perforated
from 70 to 93 ft.

Size of perforations
¼" X 3"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

PUMP INSTALLED — WATER PLENTIFUL - COLD + CLEAR - FAIR DRINKING

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. W. Cunningham
Well Driller

By Richard Hiez

License No. 180

Dated 5/5, 1956

(Not to be filled in by Driller)

OFFICE
STATE ENGINEER

1956 MAY 8 AM 10 13