

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3572
 Rec. Aug 5 1956
 Well No. _____
 Permit No. _____

Do not fill in

Owner K. A. Judge, 2001 Plater Way Driller Harvey Meyer
 Address Sparks, Nevada Address 306 Bath St. Carson City Lic. No. 10
 Location of well: $\frac{1}{4}$ $\frac{1}{4}$ Sec. 7-18, T. 18 N/S, R. 20 E, in WASHOE Washoe County
 or Sierra Menor Subdivision, South of WASHOE Reno, Nevada
 Water will be used for Domestic Total depth of well 115 feet
 Size of drilled hole 6 Inch Weight of casing per linear foot 13 lbs.
 Thickness of casing 3/16 Inch Temp. of water Cool
 Diameter and length of casing 6" ID, 115 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing
 If nonflowing well give depth of standing water from surface 22 feet
 If flowing well describe control works Not Flowing
(Type and size of valve, etc.)
 Date of commencement of well July 26, 1956 Date of completion of well July 30, 1956
 Type of well rig Cable Tools, 72 Speed Star

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	Hard Pan	
3	22	19	Sandy Clay	Chief aquifer (water-bearing formation) from <u>80</u> to <u>115</u> ft.
22	25	3	Water Sand	Other aquifers.....
25	80	55	Sandy Clay & Rock	
80	90	10	Rock	
90	115	25	Rock & Water Sand	First water at <u>22</u> feet.
				Casing perforated from <u>99</u> to <u>115</u> ft.
				Size of perforations <u>1/8" X 6"</u>



