

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 35-86
 Rec. Dec 4 1956
 Well No. 7
 Permit No. Do not fill in

Owner Bureau of Reclamation Driller Lee Harvey
 Address Winnemucca Nevada Address Box 616 Winnemucca Lic. No. 170
 Location of well: N44.5E 1/4 Sec. 6, T45 N/S, R28 E, in Humboldt County
 or on fence line of Bog Hut grazing project
 Water will be used for Stock Total depth of well 128 feet
 Size of drilled hole 6" Weight of casing per linear foot _____
 Thickness of casing 3/16" Temp. of water 67°
 Diameter and length of casing 6" x 128 feet
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 65 feet
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well Nov. 28 - 56 Date of completion of well Dec. 1 - 56
 Type of well rig Ducyrus Eric 24 L Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2 1/2	2 1/2	Topsoil -
2 1/2	19	16 1/2	Hardpanny Clay -
19	128	111	Sandy Blue silty Clay w/ thin sand streaks seeping water from 68 to 128

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from none to _____ ft.

Other aquifers
sand seams from 68 - 128

First water at 68 feet.

Casing perforated
 from 70 to 125 ft.

Size of perforations
3/16" x 6" Torch cut slots

1956 DEC 4 AM 10 22
 OFFICE OF THE STATE ENGINEER

