WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3632
Rec. Jan 3 1957
Well No.
Permit No.
Do not fill in

Owner Zarley Ben Harrison Driller Fred Eyl
Address Fallon Nev. Address E. Star Rt Fallon Nev. Lic. No. 121
Location of well: NE ¼ NE ¼ Sec. 12, T. 18 N/~~S~~, R. 28 E, in Churchill County
or

Water will be used for Domestic Total depth of well 26 ft.
Size of drilled hole 6 inch Weight of casing per linear foot
Thickness of casing 20 gauge Galvanized Temp. of water 60°
Diameter and length of casing 6 inch Casing 26 ft. long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 8 ft.
If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Dec 3 - 1956 Date of completion of well Dec 4, 1956
Type of well rig Cable Tool Well Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	adobe
2	10	8	Sand
10	12	2	adobe
12	20	8	Sand
20	26	6	gravel.

Water-bearing Formation, Casing Perforations, Etc.
Sand.

Chief aquifer (water-bearing formation)
from 20 to 26 ft.

Other aquifers

First water at 10 feet.

Casing perforated
from 18 to 26 ft.

Size of perforations
1/64 x 1 inch

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6in.	0	26	26 ft.	20 Gauge Galvinized Casing & Cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump Test about 1500 Gal per Hr

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Eth.
Well Driller

By Mrs Fred Eth.

License No. 121

Dated Dec 5, 1956

Well Drilling Contractor
Lic. No. H732.

(Not to be filled in by Driller)

OFFICE
ENGINEER

1957 JAN 3 AM 11 CO