WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3765
Rec. May 6 1957
Well No.
Permit No.
Do not fill in

Owner Sam Merritt Driller J. B. Reynolds

Address Dayton Nevada Address Fallon Nev. Lic. No. 23

Location of well: 1/4 6W 1/4 Sec 10, T 15 N/S, R 20 E, in Ormsby County

or Well is located in New Empire

Water will be used for Domestic use Total depth of well Sixty feet

Size of drilled hole Eight inch Weight of casing per linear foot eighteen lbs.

Thickness of casing 5-16 Temp. of water cold

Diameter and length of casing eight inch by sixty feet.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface eight feet

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well April 22 1957 Date of completion of well April 23 1957

Type of well rig Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	14	14	Silt & gravel
14	36	22	Sand & brown clay
36	38	2	gravel
38	44	6	Sand & blue clay
44	48	2	Blue clay
48	53	5	Gravel
53	55	2	~~XXXXX~~ Blue clay
55	60	5	Water sand & fine gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 45 to 60 ft.

Other aquifers small amount of water from 12 to 15 ft.

First water at 12 feet.

Casing perforated

from 46 to 60 ft.

Size of perforations

1" 4 By 3 in.

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J B Reynolds
Well Driller

By.....

License No. 28

Dated April 24, 1957

OFFICE
STATE ENGINEER

1957 MAY 6 AM 8 35

(Not to be filled in by Driller)