WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3770
Rec. May 10 1957
Well No.
Permit No.
Do not fill in

Owner H. L. Gifford Driller Jas Wilhyn Jr. Pitcher Co

Address Sun Valley Address 190 Moana Lane Lic. No. 260

Location of well: SE ¼ SE ¼ SW ¼ Sec. 18, T 20 N/S, R 20 E, in Washoe County

or NE cr 6th + Sun Valley Drive

Water will be used for Domestic Total depth of well 95'

Size of drilled hole 6" Weight of casing per linear foot 19#

Thickness of casing 3/16 Temp. of water 60

Diameter and length of casing 6 1/8 X 94
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 45'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Apr 5 57 Date of completion of well Apr 8 57

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Top Soil
4	65	61	Hard pack Clay + Gravel
65	90	25	Sandy Clay w/water
90	92	2	Sand
92	95	3	Clay.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 65 to 92 ft.

Other aquifers

First water at 65 feet.

Casing perforated

from 64 to 94 ft.

Size of perforations

1/8 x 6" Torch cuts

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 1/8	0	94	94	Black iron, weld on steel shoe.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail Test 15 G.P.M.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Fletcher Co
Well Driller

By [illegible]

License No. 265

Dated April 12, 1957

OFFICE
STATE ENGINEER

1957 MAY 10 AM 10 03

(Not to be filled in by Driller)