

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. May 3777  
 Rec. May 23 1957  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

Do not fill in

Owner Frank Simonario Driller H E Hansen  
 Address 706 Lake Valley Terrace Address Tempeh Lic. No. 112  
North pasture  
 Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. T. N/S, R. E, in ESMERALDA Count  
 or: #1 - SE 1/2 NE 1/4 Sec 16 T 35 R 35 E MDM  
 Water will be used for stock Total depth of well 50'  
 Size of drilled hole 8" Weight of casing per linear foot 10 g.p.  
 Thickness of casing \_\_\_\_\_ Temp. of water 63°  
 Diameter and length of casing 8" 50'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 26"  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well June 27-55 Date of completion of well June 30-55  
 Type of well rig \_\_\_\_\_

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0'	18'	18'	CLAY
18'	34'	16'	sandy clay
34'	46'	12'	PAK sand gravel
46'	50'	4'	SANDY CLAY

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 34 to 46 ft.

Other aquifers \_\_\_\_\_

---

First water at 18 feet.

Casing perforated

from 42 to 48 ft.

Size of perforations

1/8 X 1 1/2"

OFFICE  
STATE ENGINEER

1957 MAY 23 AM 10 19

