

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3818
 Rec. July 10 19 57
 Well No.
 Permit No.

Do not fill in

Owner Hugh walthers Driller Glenn McFinch
 Address Inlay, Nev. Address P.O. Box 691 Winnemucca, Nev. Lic. No. 185

Location of well: NE 1/4, NE 1/4 Sec. 8, T. 22N/6, R. 24E, in Carahing County

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 6 inch Weight of casing per linear foot

Thickness of casing 12 gauge Temp. of water cool

Diameter and length of casing 100 feet 6 inch casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 40 feet

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 10/8/56 Date of completion of well 10/12/56

Type of well rig Keystone # 51 Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	4	4	Top soil	
4	24	20	Hard Pan	
24	40	16	White Clay	Chief aquifer (water-bearing formation)
40	60	20	Blue Clay	from <u>60</u> to <u>84</u> ft.
60	84	24	Sand & Clay in thin layers (Sand water bearing)	<u>SAND</u>
84	100	16	brown clay with angular rocks (dry)	Other aquifers
<p>OFFICE STATE ENGINEER</p> <p>1957 JUL 10 AM 10 16</p>				<p>First water at <u>60</u> feet.</p> <p>Casing perforated from <u>60</u> to <u>100</u> ft.</p> <p>Size of perforations <u>1/4 x 2 chisel bit</u></p>

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Glenn McManis
Well Driller

By _____

License No. 125

Dated 7/6/57, 19____

(Not to be filled in by Driller)
