

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3840  
 Rec. July 19 1957  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner State Forester Firewarden Driller Harvey & Bob Meyer  
 Address Boynton Lane Reno, Nevada Address 306 Bath St. Carson Lic. No. 209  
 Location of well: NE 1/4 SW 1/4 Sec. 16, T. 19 N/S, R. 20 E, in Washoe County  
 or University of Nevada Boynton Lane, Reno, Nevada  
 Water will be used for Domestic Total depth of well 66 feet  
 Size of drilled hole 6" Weight of casing per linear foot 13 lbs  
 Thickness of casing 3/16" Temp. of water Cool  
 Diameter and length of casing 6" ID, 66 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing  
 If nonflowing well give depth of standing water from surface 6 foot  
 If flowing well describe control works Not Flowing  
(Type and size of valve, etc.)  
 Date of commencement of well July 3, 1957 Date of completion of well July 6, 1957  
 Type of well rig 71 Speed Star, Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	16	16	Sand & Clay
16	51	35	Sand & Rock
51	55	4	Clay
55	66	11	<del>SIA</del> Sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 41' to 66 ft.

Other aquifers \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

First water at 15 feet.

Casing perforated

from 45 to 66 ft.

Size of perforations

1/8" X 8"

OFFICE  
 STATE ENGINEER  
 1957 JUL 19 AM 10 13



