

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2900  
 Rec. Oct 22 1957  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner S.S. Rounds Driller Dave McNinch  
Box 585  
 Address Battle Mountain, Nevada Address Winnemucca, Nevada Lic. No. 219  
 Location of well:  $\frac{1}{4}$  Sec 8, T32N/S, R45E, in Lander County  
 or In town of Battle Mtn. east of Southern Pacific tracks, at new house  
 Water will be used for domestic Total depth of well 103'  
 Size of drilled hole 6" Weight of casing per linear foot 14 lbs.  
 Thickness of casing 3/8 standard pipe Temp. of water mild  
 Diameter and length of casing 6" 103'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure well flows 3 g.p.m. no pressure  
 If nonflowing well give depth of standing water from surface .....  
 If flowing well describe control works well has screw cap with 1" nipple & valve welded on  
(Type and size of valve, etc.)  
 Date of commencement of well Sept. 4, 1957 Date of completion of well Sept. 7 1957  
 Type of well rig # 71 Speed Star Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	2	2	salt grass sod	Chief aquifer (water-bearing formation) from <u>88</u> to <u>103</u> ft. Other aquifers <u>surface</u> <u>water 13 to 30</u> <u>2nd. water 33 to 54</u>  First water at <u>13</u> feet.  Casing perforated from <u>80</u> to <u>103</u> ft.  Size of perforations <u>1/8 x 6 torch slots</u> <u>approx 3 per ft</u>
2	11	9	cemented gravel hardpan	
11	13	2	yellow clay	
13	30	17	sand and fine gravel	
30	33	3	hard sandstone	
33	54	21	sand & fine gravel	
54	88	34	sticky blue clay	
88	103	15	sand & streaks of blue clay	



