

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4221  
 Rec. Aug 7 1958  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Thomas Day Driller M. Artlip

Address 172 E. 7th Ave., Sun Valley, Nev. Address 795 Lupin Dr., Sun Valley, Nev. 287

Location of well: NE 1/4 SE 1/4 Sec. 18, T. 20 N/S, R. 20 E, in Washoe County  
 or 172 E. 7th Ave., Sun Valley, Nev.

Water will be used for Domestic Total depth of well 120'

Size of drilled hole 6" Weight of casing per linear foot 7 lbs

Thickness of casing 10 ga. Temp. of water cold

Diameter and length of casing 6" by 120'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 60'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well July 14, Date of completion of well July 15, '58

Type of well rig Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Hard pan
20	83	63	Sandy clay
83	88	5	Water sand
88	100	12	Sandy clay
100	115	15	Sand, water, & clay
115	120	5	Hard sand

Water-bearing Formation, Casing Perforations, Etc.  
**Sand clay**

---

Chief aquifer (water-bearing formation)  
 from 100 to 115 ft.

Other aquifers Water sand  
88 to 88 feet.

---

First water at 83 feet.

Casing perforated  
 from 90 to 120 ft.

Size of perforations  
1/16" by 6"



