

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4830  
 Rec. Sept. 29 1959  
 Well No. \_\_\_\_\_  
 Permit No. 46705

*Do not fill in*

Owner Bureau of Land Management Driller George W. Norcutt

Address 807 N. Plaza, Carson City, Nevada Address Fallon, Nevada Lic. No. 93

Location of well: SE 1/4 SW 1/4 Sec. 22., T. 23 N/S, R. 19 E, in Storey Neshae County

Water will be used for livestock Total depth of well 224

Size of drilled hole 8" Weight of casing per linear foot 8 lbs.

Thickness of casing 1/8" Temp. of water \_\_\_\_\_

Diameter and length of casing 6" O. D.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 207

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 8/26/59 Date of completion of well 9/15/59

Type of well rig cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Clay
5	18	13	Sandy clay
18	20	2	Gravel
20	32	12	Sandy clay
32	35	3	Gravel
35	62	27	Clay
62	68	6	Sandy Clay
68	72	4	Gravel
72	105	33	Clay
105	108	3	Sandy Clay
108	112	4	Gravel
112	145	33	Clay
145	148	3	Gravel
148	170	32	Sandy clay
170	186	16	Clay
186	190	4	Sand
190	207	17	Clay
207	224	17	Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 207 to 224 ft.

Other aquifers \_\_\_\_\_

First water at 180 feet.

Casing perforated

from 195 to 224 ft.

Size of perforations

1/8 x 2"

