WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4928
Rec. Oct 30 19 59
Well No.
Permit No.
Do not fill in

Owner H. A. Bourne Driller W. E. Blair
Address Zephyr Cove Nevada Address Box 284 Lake Tahoe Lic. No. 301
Location of well: ....¼....¼ Sec. 10, T. 13 N/S, R. 18 E, in Douglas County
or 3/4 mile South of Zephyr Cove Post Office on U.S. 50. 300 ft East of U.S. 50
Water will be used for Domestic Total depth of well 55
Size of drilled hole 12" to depth of 32 ft 8" hole Weight of casing per linear foot 11.69 lbs
Thickness of casing 10 gage Temp. of water Cold.
Diameter and length of casing 8" x 52 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 12 ft
If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 10-15-59 Date of completion of well 10-19-59
Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Sandy Soil
12	17	5	Cobbles & Sand
17	32	15	Silt & gravel
32	55	23	Decomposed Granite

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 52 to 55 ft.
Other aquifers 12-17 Cobbles & Sand

First water at 15 feet.

Casing perforated
from ..... to ..... ft.

Size of perforations
none

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	51	52	1 ft above ground Open bottom well Sealed to depth of 32 ft to decomposed granite

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Test by bailing - 20 G.P.M. with 30 ft drawdown in 1 hr test

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed W. E. Blain
Well Driller

By Florence Blain Co-Owner

License No. 301

Dated 10-28, 1959

1959 OCT 30 AM 9 06

OFFICE ENGINEER

(Not to be filled in by Driller)