


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 5187  
 Rec. MAY 23 1960  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner ADAM Dolinski Driller A & B CONTRACTORS

Address E. 3rd Ave, Sun Valley Address Sun Valley, Nevada Lic. No. 287

Location of well: S. 1/4 SE 1/4 Sec. 18, T. 20 N. S. R. 20 E, in Washoe County  
 or \_\_\_\_\_

Water will be used for domestic Total depth of well 80'

Size of drilled hole 6" Weight of casing per linear foot 9 lbs.

Thickness of casing 156 ga. Temp. of water cold

Diameter and length of casing 6-5/8" X 80'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 32

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 3-23-60 Date of completion of well 3-25-60

Type of well rig cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	34	34	Open well---dug
34	68	34	sandy clay
68	78	10	sand & gravel
78	80	2	sandy clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 68 to 78 ft.  
 Other aquifers 34'

---

34  
 First water at \_\_\_\_\_ feet.

---

Casing perforated  
 from 60 to 75 ft.

---

Size of perforations  
1/8" X 6"

