

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6328
 Rec. Dec 26 1961
 Well No. _____
 Permit No. _____

Do not fill in

Owner Diemetrio Buscaglia Driller J.C. Faretto & Son
 Address 6200 Lake Side Drive, Reno, Nev. Address 736 Humboldt St, Reno Lic. No. 2
 Location of well: NW 1/4 SW 1/4 Sec. 36, T. 19 N, R. 19 E, in Truckee Meadows, Washoe County
 or 1 mile south on Lake Side Drive from Moana Lane near Evans Creek,
 Water will be used for Stock well Total depth of well 100'-00"
 Size of drilled hole 6 inch Weight of casing per linear foot 12.89 lbs.
 Thickness of casing .188 of an inch Temp. of water 50°
 Diameter and length of casing 6 5/8" O.D. Diameter, 11'-06" to 23'-05" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 38'-07"
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well November 14, 1961 Date of completion of well December 4, 1961
 Type of well rig Speed Star 71 Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
10	35	35	Small rocks & clay.
35	45	10	Yellow clay.
45	50	5	1st water. Water level 36'-07", Not much water, Yellow clay.
50	60	10	Yellow clay.
60	70	10	2nd water. Water level 39'-00", Very little water, Yellow clay with fine to coarse sand & gravel.
70	80	10	3rd water. Very little water. Yellow clay with fine to coarse sand.
80	90	10	Yellow clay.
90	100	10	4th water. Little water, Fine to medium sand, Clay formation solid & tight.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 90 to 100 ft.

Other aquifers 70 to 80

60 to 70

First water at 45 feet.

Casing perforated

from 70 to 80 ft.

Size of perforations

3/8" x 1 1/2"



