WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6841
Rec. Nov. 14 1962
Well No.
Permit No.
Do not fill in

Owner: John A. Mutz — Driller: Burroughs Electric Co.

Address: Grass Valley Road, Winnemucca, Nevada — Address: 109 E. 2nd. St. Winnemucca, Nevada — Lic. No. 257

Location of well: West ¼ East ¼ Sec. 6, T. 35 N/S, R. 38 E, in M.D.B.&.M. **Humboldt County

or

Water will be used for: House — Total depth of well: 100'

Size of drilled hole: 8" — Weight of casing per linear foot: 16 lbs.

Thickness of casing: 3/16" — Temp. of water: ——

Diameter and length of casing: 100' of 8" casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: ——

If nonflowing well give depth of standing water from surface: 60'

If flowing well describe control works: ——
(Type and size of valve, etc.)

Date of commencement of well: July 22 — Date of completion of well: July 25

Type of well rig: Bucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Topsoil
6	40	34	Rock & sand
40	73	33	Sand & gravel
73	78	5	Clay
78	100	22	Sand & gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 78' to 100' ft.

Other aquifers: 40- 73

First water at ..... feet.

Casing perforated
from 70 to 100 ft.

Size of perforations

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	100	100'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed BURROUGHS ELECTRIC CO.
Well Driller

By W. J. Lloyd
W.J. LLOYD

License No. 257

Dated NOVEMBER 13, 1962

(Not to be filled in by Driller)

1962 NOV 14 AM 9 16

STATE ENGINEER