WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7004
Rec. FEB 12 1963
Well No. [redacted]
Permit No. [redacted] 29649
Do not fill in [redacted]

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Steve E Wall Driller: B & B Drilling Co
Address: Lathrop Wells Nev Address: Beaver Utah Lic. No. 193
Location of well: NE ¼ NW ¼ Sec. 9, T/13 N/S, R 49 E, in Nye County
or
Water will be used for: IRRIGATION Total depth of well: 671'
Size of drilled hole: 24" Weight of casing per linear foot: 42 lbs
Thickness of casing: 14" Temp. of water: app 65°
Diameter and length of casing: 14" 568'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 80 ft
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well: Dec 1st 1962 Date of completion of well: Dec 12th 1962
Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	SURF.
3	22	19	SAND.
22	45	23	Sand & CLAY
45	61	16	Gravel & CLAY
61	130	69	BOULDER & CLAY
130	170	40	CLAY & SAND
170	179	9	BLOUDER & CLAY
179	186	7	CLAY & SAND
186	198	12	BOULDER & GRAVEL
198	210	12	SAND & GRAVEL
210	221	11	BOULDERS & SAND
221	241	20	Sand & Clay.
241	249	8	Boulders & Sand
249	258	9	Boulders & Gravel
258	270	12	Sand & Gravel
270	315	45	Boulders & Gravel
315	360	45	Sand & Gravel Streak of Clay
360	368	8	Clay
368	372	4	Sand & Gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 110 to 568 ft.
Other aquifers

First water at 110 feet.

Casing perforated
from 140 to 568 ft.
563

Size of perforations
5/16 to 1/2.

919