

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 7072
 Rec. Mar. 19 1963
 Well No.
 Permit No.
Do not fill in

Owner Ernest Cole Driller H & H Drilling Cont.

Address 315 6th St. Sparks, Nevada Address 580 Casazza Drive Reno Lic. No. 7124

Location of well: NW 1/4 NW 1/4 Sec 19, T.21 N/S, R.18 E, in Washoe County
 or

Water will be used for Domestic Total depth of well 101

Size of drilled hole 8" Weight of casing per linear foot

Thickness of casing .156 Temp. of water Cold

Diameter and length of casing 8 inch 101 feet
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 32 Feet

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well 2-2-63 Date of completion of well 2-10-63

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top soil
2	44	42	sand & clay Brown
44	47	3	Gravel- First water - cased off
47	54	7	Clay & sand streaks
54	70	16	Sand & gravel- no water
70	83	13	Sand & clay
83	85	2	Gravel - 2nd water about 3 g.p.m.
85	89	4	Sand & clay
89	94	5	Gravel - 3rd water
94	101	7	sand & clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 89 to 94 ft.

Other aquifers 44-47
 cased off

83-85

First water at 44 feet.

Casing perforated
 from 82 to 95 ft.

Size of perforations
1/8 by 6 inches



