

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

✓ Log No. 7151  
 Rec. May 13 1963  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
Do not fill in

Owner Royal Crowell Driller Red Top Well Drilling Co.

Address Gardnerville, Nevada Address Gardnerville, Nevada Lic. No. 407

Location of well: SW 1/4 NW 1/4 Sec 14, T. 12 N. 8, R. 19 E. in Douglas County

Water will be used for Domestic Total depth of well 102

Size of drilled hole 8 3/8 Weight of casing per linear foot \_\_\_\_\_

Thickness of casing 188 Temp. of water \_\_\_\_\_

Diameter and length of casing 8 3/8 = 102  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 20 ft

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 9/15/62 Date of completion of well 9/23/62

Type of well rig Keystone Cable

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
<u>Top</u>	<u>3</u>	<u>3</u>	<u>Top Dirt</u>	Chief aquifer (water-bearing formation) from <u>55</u> to <u>102</u> ft.
<u>3</u>	<u>20</u>	<u>17</u>	<u>D.S. &amp; clay</u>	
<u>20</u>	<u>25</u>	<u>5</u>	<u>Hard Pan</u>	Other aquifers _____
<u>25</u>	<u>52</u>	<u>27</u>	<u>Sandy Gravel fine</u>	_____
<u>52</u>	<u>55</u>	<u>3</u>	<u>Hard Pan</u>	_____
<u>55</u>	<u>102</u>	<u>37</u>	<u>Gravel &amp; fine sand</u>	First water at <u>25</u> feet.
				Casing perforated from <u>55</u> to <u>98</u> ft.
				Size of perforations <u>1/4" W x 4" long = 5 Round</u> <u>Dr. ft.</u>



