

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. <u>25734</u>
Rec. <u>19</u>
Well No. <u>I</u>
Permit No. <u>47115</u>

Do not fill in

Owner Vincent Silvestri Driller S. R. Mc Kinney & Sons, Inc.

Address 2309 Beverly Way, L.V. Address 1042 So. Main Lic. No. 45

Location of well: NE 1/4 SE 1/4 Sec. 31, T21 N/S, R62 E, in Clark Coun. Clark
or # 47115

Water will be used for Domestic Total depth of well 200 feet.

Size of drilled hole 12" to 55' 8" to 200' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 8" ID from 0 to 200'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 9'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 1-25-61 Date of completion of well 2-3-61

Type of well rig Bucyrus Erie 24 L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	48	48	Greyish blue sand
48	52	4	greyish blue sand (Water)
52	78	26	Green clay (Water)
78	92	14	clay & gravel (Water)
92	112	20	gravel & clay
112	122	10	brown clay
122	140	18	gravelly clay
140	175	35	brown gravelly clay
175	191	16	gravelly clay (Water)
191	200	9	Hard gravelly clay (Water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 191 to 200 ft.

Other aquifers 52 to 78'

48 to 52

78 to 92

175 to 191

191 to 200

First water at 48' feet.

Casing perforated

from 80 to 200 ft.

Size of perforations

3/16 x 10"



DR. 111 #

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7161
 Rec. 1955
 Well No. 19597
 Permit No. 19597
 Do not fill in

How-Stewart Water Case.

Owner J. M. Halstead Driller Patrick H. Thompson

Address 2520 Flower St. No. Las Vegas, Nev Address 217 So 26th St. W. North No. 102

Location of well: SW 1/4 Sec. 19, T. 21N/S, R. 62E, in Clark County

or SW 1/4 of said section

Water will be used for Domestic Total depth of well 220'

Size of drilled hole 8" from 120' to 220' Weight of casing per linear foot 9.25

Thickness of casing 10 gauge Temp. of water cool

Diameter and length of casing 6" - 110' length (liner)
(Casing 12" in diameter and under give inside diameter; casing 18" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure 5 G. P. M. pressure 10 1/2 P. S. I.

If nonflowing well give depth of standing water from surface

If flowing well describe control works Capped
(Type and size of valve, etc.)

Date of commencement of well Oct. 25, 1955 Date of completion of well Oct. 28, 1955

Type of well rig Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	120	120	Covered by former log
120	165	45	Red clay
165	170	5	Cemented gravel
170	210	40	Red sandy clay
210	220	10	Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 210 to 220 ft

Other aquifers None covered by this report

First water at _____ ft

Casing perforated
 from 160 to 220 ft

Size of perforations
3/16 x 12 1/2 ft

