WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7178
Rec. May 20 1963
Well No. 29254
Permit No. 29410
Do not fill in

Owner: Salvador Urrutia
Driller: Smith & Polati Inc
Address: Wadsworth Nev
Address: 195 E 6th Ave Sparks Lic. No. 207
Location of well: ¼ ¼ Sec. 3, T 20 N/S, R 24 E, in Washoe County
or Town of Wadsworth
Water will be used for: Domestic
Total depth of well: 97
Size of drilled hole: 8 5/8 OD
Weight of casing per linear foot: 16.90
Thickness of casing: 188
Temp. of water: Cold
Diameter and length of casing: 8 5/8 OD 98 feet Long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 21

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 4-11
Date of completion of well: 4-16-63
Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	Sand + Gravel
30	42	12	tight Gravel
42	73	29	Clay + Gravel
73	95	22	Firm Gravel + Water
95	97	2	Brown Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 73 to 95 ft.

Other aquifers:

First water at 30 feet.

Casing perforated
from 85 to 92 ft.

Size of perforations
1/16 X 6 6 Rows

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8 00	0	98	98	Welded Black Line Pipe Steel Shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Static Water Level 21 feet
Bailed 40 Gal per Min.
Drawdown 44 feet

Mud Grout seal top 20 feet

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Claude Pulete
Well Driller

By Claude Pulete

License No. 207

Dated 4-16, 19 63

(Not to be filled in by Driller)

1963 MAY 20 AM 9 22
OFFICE
STATE ENGINEER